

Twist Drill Series

Model	Ø Drill bit range (mm)	Tip angle range	Power Suppply	Motor Speed (R.P.M)	Supply standard wheel	Collect Series	Gross Weight (kg)	Dimensions (mm)
GP-01	Ø 2.1~Ø13	90° ~ 140°	220~240V-AC 50/60Hz	5300	CBN 200 grit for HSS drill	ER-20 with 12 pcs collects	8.0	280x133x155
GP-21	Ø 12.0~Ø25.4			3280		ER-32 with 15 pcs collects	22.0	365x204x223

End Mill Sharpening & Cutting Series

Model	Ø Drill bit range (mm)	No. of flutes sharpened	Power Suppply	Motor Speed (R.P.M)	Supply standard wheel	Collect Series	Gross Weight (kg)	Dimensions (mm)
GP-06	Ø 3.0~Ø12	2-,3- and 4 flutes of square shape	220~240V-AC 50/60Hz	5300	SD 200 grit x 3 pcs for solid carbide	ER-20 with 6 pcs collects	15.7	300x165x245
GP-26	Ø 10.1~Ø26			4600	SD 200 grit x 4 pcs for solid carbide	ER-32 with 15 pcs collects	28.0	510x290x270
GP-13	Ø 3.0~Ø16	Cutting Material: Solid Carbide or HSS		250W /5000	E100SDC-115 (for solid carbide) E60WA(Ø100) (for HSS)	NA	29.5	380x230x220

Optional Parts

GP-01	SD/ CBN 200 grit grinding wheel
GP-21/GP-26	SD/ CBN 200 grit grinding wheel
GP-06	SD/ CBN 200 grit grinding wheel
GP-01/GP-06	ER20 collect
GP-21/GP-26	ER32 collect
GP-1/GP-6	ER20 0.5 point End Mill Shank collect (2.5mm~11.5mm /10 pcs)
GP-13	E100CBN-115 for HSS